

WARRANTY POLICY & OWNER'S GUIDE

Revision 2026.1 • Effective 08/28/2026 • Supersedes Política de Garantía Vimetal 2024

Warrantor: JCV Trailers LLC • Fabricator: Vimetal Trailers • United States

Document	Contents
Part A	Limited Warranty Policy — coverage, exclusions, conditions, and claims
Part B	Delivery & Acceptance Record — unit identification and accessory checklist
Part C	Owner's Guide — pre-tow checklist, maintenance, tire and load capacity charts

This document is issued by JCV Trailers LLC ("JCV"), the warrantor and seller of Vimetal trailers in the United States. Vimetal Trailers is the fabricator. Parts A, B, and C form a single agreement. Retain this document together with your invoice — both are required to make a warranty claim.

3-YEAR STRUCTURAL WARRANTY — VALID IN OFF-ROAD USE

Your Vimetal trailer is built to haul race and off-road vehicles. This warranty stays in effect when the trailer is operated over unimproved roads, gravel, washboard, and desert terrain consistent with its design, provided it is loaded within the capacity printed on the unit.

Quick Reference

If you need to...	Do this
Make a warranty claim	Notify JCV in writing within the warranty period. Send serial number, invoice, photos, and a description to svc@vimetal.mx .
Know what is covered	See Part A, Section A1.
Know what is not covered	See Part A, Sections A3 and A4.
Keep coverage valid	Follow the maintenance schedule in Part C, Section C2.
Check load limits	See the Load Capacity Chart in Part C, Section C4.
Transfer the warranty	Notify JCV in writing within 30 days of sale. See Part A, Section A7.

PART A — LIMITED WARRANTY POLICY

A1. Coverage at a Glance

What	How long	From
Structure: chassis, frame welds, tongue, crossmembers, rails, axle mounts	3 years	Invoice date
Other parts manufactured by Vimetal	2 years	Invoice date
Factory finish application defects (see A3)	90 days	Delivery date
Tires, rims, leaf springs, hubs, bearings, spindles, lights, jacks	Original manufacturer's warranty	Per that manufacturer

A2. What Is Covered

JCV Trailers LLC warrants each new Vimetal trailer it sells against defects in manufacturing and in material, under normal use, for the periods stated in A1. JCV reserves the right to decide whether a covered defect is repaired or the defective material replaced.

Structural coverage includes welds in the trailer structure, provided the trailer has not been overloaded and the maintenance required by this policy has been performed.

A3. What Is Not Covered

Parts warranted by their own manufacturer

Tires, rims, leaf springs, hubs, bearings, spindles, lights, jacks and other accessories that are not manufactured by Vimetal assembled into the trailer are warranted by their manufacturers and are excluded from this limited warranty. JCV will assist you in directing the claim to the correct manufacturer.

Parts and conditions excluded entirely

- Floors and wood decking.
- Paint and finish, except for a documented factory application defect — such as blistering, delamination, or adhesion failure — reported in writing within 90 days of delivery. Corrosion, oxidation, chipping, abrasion, and chemical or environmental damage are not covered at any time.
- Parts requiring replacement in the normal course of use due to normal wear.
- Any accessory or component not supplied by JCV or Vimetal.

Causes excluded

This warranty covers only defects in original components arising from normal use. It does not apply where the trailer has been subjected to negligence, accident, abuse, misuse, or overload, or has been repaired or altered without JCV's prior written consent. It does not apply if the trailer is used as a rental unit.

A4. Causes That Void This Warranty

1. The trailer has been modified, repaired, or altered in any way without JCV's express written consent.
2. The trailer has been loaded beyond the capacity printed on the unit and shown in the Load Capacity Chart in Part C.
3. The required maintenance described in Part C was not performed, and the defect claimed is one that the maintenance would have prevented.
4. The trailer suffered an accident or was subjected to negligence by the user.
5. Special coating for the owner's geographic region was not requested at the time of order, and corrosion appears earlier as a result.
6. The trailer is used as a rental unit.

A5. Conditions of Coverage

- Notify JCV in writing within the warranty period of any defect, and provide any evidence JCV may reasonably request.
- Present the original invoice. The warranty cannot be validated without it.
- Operate and maintain the trailer in accordance with good practice and the recommendations in Part C of this document.
- Distribute the load across the full surface of the trailer bed. The structure, chassis, crossmembers, rails, tongue, and axles are designed to carry the manufacturer's stated weight distributed across that area. Load forces effectively double when the trailer travels over rough terrain.
- JCV strongly recommends an annual service inspection at a JCV or Vimetal facility. This inspection is billed separately and is not required to keep this warranty in effect.
- Trailers that carry hazardous chemicals or flammable substances — including fuel tankers and tank trailers — must be delivered empty and washed before any warranty work can be performed.

This warranty does not require you to use Vimetal or JCV replacement parts, and it does not require you to purchase JCV or Vimetal service, in order to remain in effect. Damage caused by a part or repair not supplied or authorized by JCV is not covered, and damage that the maintenance in Part C would have prevented remains excluded.

A6. Claims and Repairs

Warranty work consists of repairing or replacing parts at a JCV Trailers LLC facility or a location JCV designates. Work performed anywhere else is reimbursable only if JCV authorizes it in writing beforehand.

The customer is responsible for bringing the trailer to JCV for inspection. In the event of an accident or damage, JCV is not obliged to collect the trailer or to send employees to inspect it on site. JCV is not responsible for transport costs to or from the customer.

Once the trailer is received, JCV has 30 days to evaluate it and reach a diagnosis. If warranty coverage applies, the work will be performed and the customer informed within that period. If coverage does not apply, JCV will issue a repair quotation, and no work will begin until the customer accepts it.

A7. Limitations and Disclaimers

IN NO EVENT SHALL JCV TRAILERS LLC BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY NATURE. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE LIMITED IN DURATION TO THE PERIODS STATED IN SECTION A1.

Some states do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

JCV Trailers LLC has only the warranties described in this document. No dealer, sales representative, employee, or agent is authorized to modify this warranty or to make any promise on JCV's behalf beyond these terms. Statements made in conversation, correspondence, advertising, or on social media do not form part of this warranty.

The remainder of the structural warranty period transfers to a subsequent owner if JCV receives written notice of the transfer — serial number, transfer date, and the new owner's name and contact details — within 30 days of the sale. All other coverage terminates on sale.

This warranty is governed by the laws of the State of [STATE], without regard to its conflict-of-laws rules, and by the federal Magnuson-Moss Warranty Act.

PART B — DELIVERY & ACCEPTANCE RECORD

B1. Unit Identification

Field	Detail	Field	Detail
Customer		Serial number (VIN)	
Invoice no.		Invoice date	
Model		Year	
Dimensions		Color	
Capacity		GVWR	
Fabricator	Vimetal TRAILERS	Delivery date	

B2. Accessories Delivered

Mark each item received with the unit.

Item	✓	Item	✓
Ramp		Hitch pin	
Toolbox		Jack wheel	
Spare tire carrier		Spare tire & rim	
Light connector		Brake controller	
Emblems		Tie-down straps	

B3. Customer Acceptance

I confirm that I have received the unit described above, with the accessories marked, in perfect operating condition. I confirm that I have received and read the JCV Trailers LLC Warranty Policy and Owner's Guide, and I accept its terms.

JUAN CARLOS VIDAURI AGUILERA
General Manager — JCV Trailers LLC

Customer name / signature
Date: _____

PART C — OWNER'S GUIDE

C1. Before Every Tow

1. Confirm the hitch ball is the size marked on the coupler and is securely fastened to the tow vehicle. Latch the coupler fully and always install a safety pin.
2. Attach the safety chains to the tow vehicle frame, crossed beneath the coupler.
3. Connect the trailer light cable and confirm all lights function.
4. Fully retract and raise the jack before moving, so it is not bent in transit.
5. Check tire pressure. This is a load-carrying trailer — correct pressure is critical to safe operation.
6. Confirm the lug nuts are correctly torqued, especially before long trips or heavy loads.
7. Secure and level the load so the trailer handles predictably under hard braking, and so weight is also felt by the tow vehicle.

C2. Scheduled Maintenance

Interval	What to do
Every 6 months (by usage)	Inspect suspension — leaf springs, hangers, equalizer, U-bolts and other critical points.
Every 6 months or 10,000 km	Inspect hubs, spindles and bearings. Check for play in the hub, confirm bearings are properly greased, and verify all parts are in good condition — seal, cotter pin, nut and dust cap.
Every 12 months	Recommended: full service inspection at a JCV or Vimetal facility (see A5).
Ongoing	Avoid potholes, severe speed bumps and irregular roads. Under load, axles carry double the force in vibrating motion and may deform or fracture.

C3. Tire Safety Chart

Tire size	Ply rating	Load capacity	Cold inflation
ST175/80 R13	6	1,660 lb (753 kg)	50 psi
ST205/75 R15	6	1,820 lb (826 kg)	50 psi
ST225/75 R15	8	2,540 lb (1,152 kg)	65 psi
ST235/80 R16	10	3,520 lb (1,597 kg)	80 psi

Inflate tires cold. Never exceed the maximum pressure marked on the tire sidewall.

C4. Load Capacity Chart

Axles	Rating per axle	GVWR (lb)	GVWR (kg)
1	3,500 lb	2,990	1,356
2	3,500 lb	7,000	3,175
1	5,200 lb	5,000	2,268
2	5,200 lb	9,990	4,532
1	7,000 lb	7,000	3,175
2	7,000 lb	14,000	6,350

GVWR is the maximum combined weight of the trailer and its load. Never exceed the rating printed on your unit. Load forces effectively double over rough terrain.